



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Address	Salgglas Zrt Budapesti 29 3104 Salgotarjan (Nograd)
Country	Hungary
Phone	0036 32 440 655
Fax	0036 32 440 168
Internet	www.salgglas.hu
Employees	380
Turnover	11.000.000
Certificates	ISO 9001:2000, ISO/TS 16949:1999, ISO/TS 16949:2002
Year founded	1996

CONTACT PERSONS

Contact 1. Mr. Balázs Kállai

CEO

Phone: 0036 32 440 655 Fax: 0036 32 440 168

Contact 2. Mr. Janos Kövi

Head of purchasing

Contact 3. Mr. Gyula Gaal

Managing Director Phone: 0036 32 440 655 Fax: 0036 32 440 474

Contact 4. Mr. Zsido

Commercialand Quality Assurance Director

Phone: 0036 32 440 655 Fax: 0036 32 440 168

glassglobal

Community



PRODUCTS OR MACHINERY LAMINATED SAFETY GLASS

Two- or more-layer glass structure the sheets of which are held together with high tear resistance, flexible PVB foil.

If broken, the glass sheet is held together by the internal foil, preventing the fragments from causing injuries. This kind off glass is made in flat ant bent construction, with or without screen-printing.

Major physical parameters:

Bending and breaking strength: 30-40 MN/m² Penetration strength: 85 N mm Heat resistence: max. 100°C, max. of 120 min.

Depending on the number of layers, foil thickness, glass thickness and the symmetry of the compund..

Available dimensions:

Thickness of glass: 4 - 33 mm Smallest: 200 x 400 mm Largest: 1605 x 2000 mm (flat) 1610 x 2500 mm (bent)

Possible areas of application:

Windscreens for motor vehicles, heavy machinery and railways cars; for architectural purposes (inner and outer glass), furniture, as well as for table sheets.

Anti-burglary and bullet-proof glasses (DIN 52290)

TEMPERED SAFETY GLASS

One-layer glass in which a tension structure is generated by heat treatment. As a result, mechanical strength increases six to eight-fold, while thermal resistance also improves.

When broken, it fragments into tiny pieces which do not cause injuries. This kind of glass comes in flat and bent construction, with or without screen-printing.

Available in the following dimensions: FLAT GLASSES

Thickness of glass: 3 - 12 mm Smallest: 100 x 200 mm Largest:

Largest: 1240 x 2400 mm

Available in the following dimensions:

BENT GLASS

Thickness of glass: 3 - 6 (8)mm Smallest: 100 x 200 mm Largest: 1200 x 1800 mm

Possible areas of applications:

For side- and rear windows of cars and trucks, as well as front windscreens of heavy machinery, windows for household appliances, for furniture and for architectural

COMPANY BACKGROUND / HISTORY

SALGGLAS is the largest vehicle-industrial glass manufacturer of Hungary. 110 years of experience in the area of glass production. Our product is tempered and glued safety glass. Burglar-proof, hurl-proof and bullet-proof glass.





Company Profile of Salgglas Zrt

A service of glassglobal.com, an affiliate of glassglobal group.

The address material you printed out is copyright and belongs to the Company or to its third party Marketing Agency, and all rights are reserved. Any User who accesses such material may do so only for its own personal use, and the use of such material is at the sole risk of the User. Redistribution or other commercial exploitation of such address material is expressly prohibited. Where such address material is provided by a third party, each User agrees to observe and be bound by the specific terms of use applying to such news material. Glass Global does not represent or endorse the accuracy or reliability of any of the info contained in any address or external websites referred to in this printout.www.glassglobal.com - The International Portal to the Glass Industry - OGIS GmbH