



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that OKDetails

Address	Rongju Machinery & Electronic Co.,Ltd No.3 liji lane,
	2nd xiaobian industrial area, 523840 Dongguan
Country	China (People´s Republic)

PRODUCTS OR MACHINERY

Specifications: Operating Temperature Range:-50~+105 Degree Celsius. Rated Voltage Range:6.3v~100v DC. Nominal Capacitance Range:0.47uF~1500uF Capacitance Tolerance: ±20%(126Hz, ±20Degree Celsius) Leakage Current:1≤0.01CRUR(uA)or 3uA whichever is greater(after 2minutes) Dissipation Factor(120Hz 20C):Ur(V) 6.3~100, tg\$:0.12~0.30 Load Life: After applying rated voltage for 2000 hours at +105C and then resumed 16 hours, the capacitor shall meet the following limits: Capacitance Change ≤±30% Initial measured value Leakage ≤Initial specified value Dissipation Factor ≤300% of initial specified value Shelf Life: After storage 1000 hours at +105C and then resumed 16 hours, the capacitor shall meet the following limits: Capacitance Change ≤±30% Initial measured value Leakage ≤200% of Initial specified value Dissipation Factor ≤300% of initial specified value Resistance to soldering Heat: The capacitors shall be kept on the hot plate maintained at 250C for 30 seconds. After removing from the hot plate and restored at room temperature, then meet the following requirement: Capacitance Change ≤±10% Initial measured value Leakage ≤Initial specified value

Dissipation Factor ≤Initial specified value

Company Profile of Rongju Machinery & Electronic Co.,Ltd

A service of glassglobal.com, an affiliate of glassglobal group.

The address material you printed out is copyright and belongs to the Company or to its third party Marketing Agency, and all rights are reserved. Any User who accesses such material may do so only for its own personal use, and the use of such material is at the sole risk of the User. Redistribution or other commercial exploitation of such address material is expressly prohibited. Where such address material is provided by a third party, each User agrees to observe and be bound by the specific terms of use applying to such news material. Glass Global does not represent or endorse the accuracy or reliability of any of the info contained in any address or external websites referred to in this printout.www.glassglobal.com - The International Portal to the Glass Industry - OGIS GmbH