

Have you ever heard about ACMOS patch for your delivery system?




ACMOS 43-5004

Is a **water-based** coating you can apply on areas in your delivery where the chute coating is worn by the glass gob **without removing** the chutes from the production to maximize the gob delivery performance!

Your advantages at a glance:



The chute coating worn by the glass gob can be repaired without removing the chutes from the production!




Loading marks, washboards etc. can be reduced to a minimum and the speed of the gob can be improved to the original level.



No negative impact on the geometry of the chutes.
No cooling down of the blacks due to the rejected glass gob.

Chute repair in 5 easy steps:

1. Shake up the contents of the can.
2. Chose the right size of the swab.
3. Remove loose dirt from the chute.
4. Soak the swab with ACMOS coating and squeeze it out so that the material doesn't drip off.
5. Reject a gob and pull the swab from the top to the bottom through the chute.



An application of every 4 hours is sufficient.
Lifetime extension of the chutes guaranteed!

Please note: The chutes should have a temperature of min. 80°C. Only then the coating dries immediately, forms a firm layer, and adheres well

Contact us for a quotation or a free of charge sample!

Marina Littau

Marketing & Sales Manager:
Phone: +49(0)421/5189-212
E-Mail: mlittau@acmos.com



ACMOS CHEMIE KG

Industriestr. 49
D-28199 Bremen

Tel: +49 421/ 5189-0
Fax: +49 421/ 511415

E-Mail: acmos@acmos.com
Homepage: www.acmos.com