glassglobal Community

glassglobal Group

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Address	**Strutz International, Inc.** 440 Mars-Valencia Road PO 509 PA 16046 Mars
Country	USA
State	Pennsylvania

PRODUCTS OR MACHINERY

Supplier of Machines for Screenprinting, Labeling

STRUTZ 6-SR-12 Industrial Container Decorator

The 6-SR-12 is a heavy duty decorator designed for 360 degrees screen printing on industrial size containers and pails up to six gallon capacity. It is manually loaded and unloaded and is capable of speeds of up to fifteen per minute.

6-SR-12 Specifications

10-15 container per minute decorating speeds
36 inch maximum screen stroke
12 inch maximum container diameter
Electrical requirements: 115 VAC/60 Hz @ 15 Amps
Pneumatic requirements: 80 PSI, 20 CFM

STRUTZ CS100 Body/Shoulder Glass Decorator

The CS-100 decorating machine decorate beverage bottles in one, two or three body and shoulder colors at speeds up to 100 bottles per minute. The patented Strutz bottle Carrier allows full adjustments in both diameter and height. The CS-100 features single registration for between-the-seams label location. Its automatic interlock insures color-to-color registration of labels eliminating any need to re-register.

CS-100 Standard Features

Available in two or three color models
Handles ware from 1-3/4" to 3-1/4" diameter and 3" to 13-1/2" height
Heavy duty construction, designed for 24 hour operation
Operates at speeds up to 100 bottles per minute with power infeed and outfeed
Capable of decorating beverage and cosmetic bottles
Fast job changeover, generally less than 45 minutes
Automatic interlock insures color-to-color registration
Captive chuck carriers designed with easily adjustable finish holders and snap-on/snap-off base cups
Pre wired and plumbed for electical and pnuematic hook-up
Air squeegees permit dial-in pressure for consistent quality decoration
Individual precision stroke setting accomplished quickly and easily
Air operated bottle steady
Single registration elimiates the need to re-register
Standard 10 HP, 230/460 VAC drives can operate auxiliary equipment
Capable of using organic and inorganic colors in heated screen units
Electrical safety system with pin point indicating lights
low maintenance costs

CS-100 Optional Features

Storage conveyor and single liner
Lehr pullbar stacker and pushbar stacker
Heated color dispensing pots

Company Profile of **Strutz International, Inc.**

A service of glassglobal.com, an affiliate of glassglobal group.

The address material you printed out is copyright and belongs to the Company or to its third party Marketing Agency, and all rights are reserved. Any User who accesses such material may do so only for its own personal use, and the use of such material is at the sole risk of the User. Redistribution or other commercial exploitation of such address material is expressly prohibited. Where such address material is provided by a third party, each User agrees to observe and be bound by the specific terms of use applying to such news material. Glass Global does not represent or endorse the accuracy or reliability of any of the info contained in any address or external websites referred to in this printout.www.glassglobal.com - The International Portal to the Glass Industry - OGIS GmbH