



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Address	Xi´an Aofa OptoelectronicsTech. Faraday Rotator/Magneto-Optic Glass No.126, Jin Hua North Road 710032 Xi´an
Country	710032 Xi′an China (People´s Republic)

## PRODUCTS OR MACHINERY

Faraday Roatator Glass is widely used especially in high-power optical rotator and isolator with large aperture, circulators, switches, polarimeters, magneto-optics sensor, high-power laser systems and other wanted Faraday Effect, etc. The main products as follow, please see Faraday Roatator Glass is widely used especially in high-power optical rotator and isolator with large aperture, circulators, switches, polarimeters, magneto-optics sensor, high-power laser systems and other wanted Faraday Effect, etc. The main products as follow, please see Faraday Roatator Glass is widely used especially in high-power optical rotator and isolator with large aperture, circulators, switches, polarimeters, magneto-optics sensor, high-power laser systems and other wanted Faraday Effect, etc.

The main products as follow, please see Product Catalog for details.

\* Diamagnetic Faraday Rotator Glass.Type MR1 with very important properties, its high Verdet constant 0.071~0.075min/Oe\*cm at 632.8nm,it's independent of temperature from -50°~+135° with better thermal stability and widely used in magneto optical sensor and Magnetic-Optical Current Transducer (MOCT), etc.

\* Paramagnetism Faraday Rotator Glass/Magneto-Optical Glasses

Type MR3-2, Verdet constant -0.329 min/Oe-cm at 632.8nm or -95.7 rad/T\*m at 632.8 nm

Type MR3, Verdet constant -0.34 min/Oe-cm at 632.8nm or -98.9 rad/T\*m at 632.8 nm

Type MR4, Verdet constant -0.38 min/Oe-cm at 632.8nm or -110 rad/T\*m at 632.8 nm

MR3 and MR4 are the highest Verdet constant in the market available exclusively from XAOT

\* Faraday Rotators Rods with high sensitive and steady which are used for all kinds of magneto optical device and instruments.

Product Description Faraday Rotator Glass / Magneto Optical Glass

Since glass material in high power laser system is damaged as a consequence of self-focusing, low non-linear refractive index as well as high Verdet constant are important factors for Magneto-Optical Glass

Our world-leading Magneto Optical Glass with very high Verdet factor, we supply them with the shape or size of your choice

Very large plates/disks/rods from diameter 1.00 mm to 300 mm are available

Faraday Rotator Glass / Magnetic Optical Glass mainly used in faraday rotating components,fabricating optics-isolators,faraday rotators,circulators,magneto-optical modulators,optical switchs,interleavers,laser gyroscopes,goniometric devices magneto-optic storage and optical information process system,current measuring transducers for magnetic field measuring and high-voltage transmission line,new generation current sensors,wave guides, iatrology,spaceflight control,satellite survey and other functional devices

Faraday Rotator Glass is made with more advanced technologies, so is performance stabilization, sensitive, and inherently immune to interfere. In comparison with artificial crystal, it is inexpensive and easy to get big size block, it has been made into different types of optical fibers, so it's widely used in many fields

Specifications The Properties of MR3-2 Faraday Rotator Glass / Magneto-Optical Glass

At 20 ° temperature Verdet Constant -0.329min/Oe\*cm or -95.7rad/T\*m at 632.8 nm Verdet Constant -0.108 min/Oe-cm or -31.4 rad/T\*m at 1064 nm

Transmission window:400nm-1600nm

glassglobal Community



Refractive indices ND=1.7441 Nd=1.7442 NF=1.7544 Nc=1.7400 N1064=1.7178

Optical Quality( $\triangle n$ ) /cm < 1x10\*-6.

Abbe number: VD=51.7 Vd=51.0

Nonlinear refrective index n2 (x10\*-13 e.s.u.)=2.74

Figure of merit V632.8 (nd/n2)=0.62

Density (g/cm\*3):4.92

Transformation temperature Tg: 788°

Sag temperature Ts:  $824^{\circ}$ Coeff.of linear thermal expansion:  $0 - 300^{\circ} (10^*-7)^{\circ})=62.6$  $100 - 300^{\circ} (10^*-7)^{\circ})=68.2$ Transparence rate T%  $\geq 86\%$  (Uncoated) Transparence rate T%  $\geq 98\%$  (Coated)

Absorption coefficients < 0.002/cm at 1064nm.

Thermal conductivity=48.10/ °(0-100 °)

dv/dt=0.0016(0-40 °) dv/dt=0.0006(40-80°)

Bulk laser<

Company Profile of Xi'an Aofa OptoelectronicsTech.

A service of glassglobal.com, an affiliate of glassglobal group.

The address material you printed out is copyright and belongs to the Company or to its third party Marketing Agency, and all rights are reserved. Any User who accesses such material may do so only for its own personal use, and the use of such material is at the sole risk of the User. Redistribution or other commercial exploitation of such address material is expressly prohibited. Where such address material is provided by a third party, each User agrees to observe and be bound by the specific terms of use applying to such news material. Glass Global does not represent or endorse the accuracy or reliability of any of the info contained in any address or external websites referred to in this printout.www.glassglobal.com - The International Portal to the Glass Industry - OGIS GmbH